

SEMANTIC MARC, MARC21 AND THE SEMANTIC WEB

Rob Styles

Talis

Knight's Court, Solihull Parkway
Birmingham, B37 7YB
+44 (0) 870 400 5000
rob.styles@talis.com

Danny Ayers

Talis

Knight's Court, Solihull Parkway
Birmingham, B37 7YB
+44 (0) 870 400 5000
danny.ayers@talis.com

Nadeem Shabir

Talis

Knight's Court, Solihull Parkway
Birmingham, B37 7YB
+44 (0) 870 400 5000
nadeem.shabir@talis.com

ABSTRACT

The MARC standard for exchanging bibliographic data has been in use for several decades and is used by major libraries worldwide. This paper discusses the possibilities of representing the most prevalent form of MARC, MARC21, as RDF for the Semantic Web, and aims to understand the tradeoffs, if any, resulting from transforming the data. Critically our approach goes beyond a simple transliteration of the MARC21 record syntax to develop rich semantic descriptions of the varied things which may be described using bibliographic records. We present an algorithmic approach for consistently generating URIs from textual data, discuss the algorithmic matching of author names and suggest how RDF generated from MARC records may be linked to other data sources on the Web.

Keywords

MARC, MARC21, RDF, Semantic Web, Data Conversion, Inferred Semantics.

1. INTRODUCTION

A great deal of data exists as strings of text in structured form within binary file formats. Imagine all the ID3 tags on MP3s or all the EXIF tags in jpeg images. A more complex variation is the bibliographic data created by the hard work of generations of librarians; getting at that data is the purpose of this paper. The principles described here, though, are equally applicable to any form of data where humans are left to infer meaning from literal strings.

The MARC standard for exchanging data has been around for more than 30 years. It is a structured binary format that has allowed libraries to exchange bibliographic data very successfully. So successfully, in fact, that the Library of Congress and British Library have around 10 million records in this form each. Most national libraries have a similar number. OCLC Worldcat, a US database of libraries' information has many tens of millions. This data is not readily available for re-use outside of the library community. Talis has, for more than 40 years, maintained a database of such bibliographic records currently numbering in the tens of millions, a mixture of contributed data from libraries and commercial data from suppliers.

The Semantic Web, a web of data linked through the use of URIs and accessible over HTTP, offers the opportunity to create large, interconnected sets of data.

This paper aims to discuss the possibilities of representing the most prevalent form of MARC, MARC21, as RDF for the Semantic Web.

2. MARC21

MARC21 is used to describe several different types of record in library catalogues. Bibliographic records describe publications, Authority records list the known forms of authors' names, titles or subject headings. All of the major library management systems in use in english-speaking countries are able to import and export data in this form.

There are other flavors of MARC; DanMARC, UNIMARC and UKMARC are just some examples. The different MARC standards all share an underlying record syntax, ISO2709, but vary in the semantics assigned to different parts of the record. They differ in the level of granularity at which they store data, a single name field versus separate fore and surnames being one example, and also in where they locate data within a record - that is what meaning is assigned to each position.

China, an increasing source of online knowledge due to their massive digitization projects, use a mixture of MARC21, CMARC and CNMARC. With the volume of data available in MARC21 and the global connectivity provided by the internet, MARC21 is rapidly becoming the lingua franca for libraries globally. The techniques described in this paper are equally applicable to all flavors of MARC as well as other data formats.

[Copyright notice to go here](#)

```
00673nam a2200217 a 45040010033000000030009000330
0500170004200800410005901500190010002000170011903
5001700136040003100153082001600184100001900200245
0062002192600033002813000020003146500060003346500
031003946550030004259cbb7fc3a7346d99c281979d45b6
79cUK-BiTAL20050705133033.0990831s1999 enk
j 000 ||eng|d aGB99Y57412bnb a0747542155 :
a()0747542155 aStDuBDS$cStDuBDSdUK-BiTAL04a823.
9142211 aRowling, J. K.00aHarry Potter and the pr
isoner of Azkaban /cJ.K. Rowling. aLondon :bBloom
sbury,c1999. a317p. ;c21 cm. 0aPotter, Harry (Fi
ctitious character)vJuvenile fiction. 0aWizardsvJ
uvenile fiction. 7aChildren's stories.2lcs
```

Figure 1. A MARC21 record in ISO2709 Syntax.

A typical MARC21 record will contain the title of the publication, the name of the creator and other contributors and often subject classifications. The underlying format was designed in the late 60's as an interchange format between machines, but due to its longevity the language of the format has become the language of the data also.

Many people find the format difficult to understand, but once the basic structure is understood it can be put to the back of the mind as there are many free and open-source tools for manipulating and getting access to this data format.

A typical MARC21 record in its native form is shown in figure 1, this form is obviously meant to be parsed by machines. A more readable representation of the same record is shown in figure 2.

```
=LDR 00673nam a2200217 a 4504
=001 9cbb7fc3a7346d99c281979d45b679c
=003 UK-BiTAL
=005 20050705133033.0
=008 990831s1999\\enk j\\000||eng|d
=015 \\$aGB99Y5741$2bnb
=020 \\$a0747542155 :
=035 \\$a()0747542155
=040 \\$aStDuBDS$cStDuBDS$dUK-BiTAL
=082 04$a823.914$221
=100 1\\$aRowling, J. K.
=245 00$aHarry Potter and the prisoner of
Azkaban /$cJ.K. Rowling.
=260 \\$aLondon :$bBloomsbury,$c1999.
=300 \\$a317p. ;$c21 cm.
=650 \0$aPotter, Harry (Fictitious character)
$vJuvenile fiction.
=650 \0$aWizards$vJuvenile fiction.
=655 \7$aChildren's stories.$2lcs
```

Figure 2. A MARC21 record shown in human-readable form.

In this form we can see the structure, down the left a series of fields, each given a 3 character identifier. We can tell from those marked '=650' that field identifiers are not necessarily unique

within a record. The later fields, from '=015' onwards have two characters of data followed by a number of subfields - each subfield starts with a \$ and a single character code such as '\$a'. A little knowledge of the publication in question allows us to pick out the author's name (100 \$a and 245 \$c), the title (245 \$a), some subjects (650 \$a), the publisher (260 \$b) and the year of publication (260 \$c). The 001 field is a special case in the standard, it is both mandatory and non-repeatable and contains a control number for the record that should be unique within a collection of records.

In addition to the field and subfield structure, the order that fields occur can also be important. The ISBN (seen here in 020 \$a), for example, may be repeated; the first occurrence being the main ISBN of the material, subsequent ISBNs being related to it in some way.

This record structure is so well established within the library domain that many people speak in terms of the field and subfield codes when discussing the art of cataloguing. The specification undergoes regular revision; the MARC21 standard is the latest revision in a long line of revisions previously called USMARC. The standard is managed by the Library of Congress [8].

That MARC21 standard is solid, well used and well understood standard within the library domain.

3. RDF AND SEMANTIC WEB

The Resource Description Framework (RDF) is a suite of W3C specifications* which offers a model of information based on logical relationships between entities known as resources. These relationships are expressed as sets of statements (triples) in the form *subject, predicate, object*, where the object provides a value of the subject for the given property (predicate). Because the object of one statement may be the subject of another, sets of statements may also be considered graph structures, in which the subjects and predicates appear as nodes linked by (property) arcs.

RDF's notion of a resource is closely related to the resource as found on the Web identified by Uniform Resource Identifiers (URIs). A node in an RDF graph may be a URI with an optional fragment identifier (this generalization is known as a URI reference), a literal value, or blank (having no form of identification independent of the local graph). Properties are always URI references.

This core model is built upon by RDF Schema[†] (RDFS) and the Web Ontology Language[‡] (OWL), and together they can be used as a versatile yet relatively straightforward description language.

The entity-relationship model of RDF is eminently suitable for expressing data. In fact RDF stores are in many ways comparable

* <http://www.w3.org/RDF/>

† <http://www.w3.org/TR/rdf-schema/>

‡ <http://www.w3.org/TR/owl-semantics/>

to relational databases, to the extent of supporting a SQL-like query language, SPARQL*. A key difference is that URIs provide a global naming scheme which allows immediate interoperability between any data sets expressed in RDF. Because in principle anything can be considered a resource, RDF can directly describe any thing, such as real-world objects, people, places or even abstract concepts.

The Web is primarily a massive, distributed document repository. It appears as a cohesive whole thanks to the use of URIs as identifiers, which allow links between documents to be created within a global context. The HTTP protocol allows navigation of this space, either directly in the browser or with the aid of search engines which index documents while crawling the hypertext space. Relational databases are commonly used to store information on the Web, but typically that information is only exposed as HTML, destined for human consumption through the browser.

RDF has various serialization formats (such as RDF/XML) through which it can be exposed directly on the Web as documents. However, because it uses URI references as identifiers, a greater degree of integration with the Web is possible compared to typical data representation languages. The web of documents that prevails today uses hyperlinks to create relationships between documents, the relationships between resources in RDF are exactly the same, allowing the web of documents to interlink with a new web of data or semantic web.

On the traditional Web, where a document resource is identified with a HTTP URI, the URI may be 'dereferenced' using the HTTP protocol to obtain a representation of that resource. Although there are certain complications, the same basic follow-your-nose mechanism can be used to link data. A HTTP URI for an entity (or relationship) can be dereferenced to find out more about an entity (or relationship).

The ontological constructs of RDFS and OWL also allow semantic 'linkage' to be expressed. A particularly useful example is the owl:sameAs property, which can be used to state that a resource with one URI is the exact same individual entity as that identified with another URI. With these technologies, data from different sources can easily be connected together and treated as a whole.

Clearly a major part of the success of the traditional Web is due to the benefits people gain through interlinking both within their own documents and into the wider system. For minimal cost, their material becomes discoverable and accessible to a global audience, and the information it contains is augmented by its linkage to and from other documents. The intuition of the Semantic Web is that benefits of a similar nature (though potentially of significantly greater magnitude) will be apparent due to the network effect of linked data.

While it is still early days, the work of the Linking Open Data community [3], which has linked together 30 or so sizable data

sets in this fashion (as of October 2007, comprising two billion RDF triples, interlinked by around 3 million RDF links), suggests that not only is this approach technically feasible, but that it will enable a whole new range of data-driven applications.

4. APPROACH

The work described in this paper was intended to develop an understanding of how the resources described in bibliographic data could be described using RDF and to understand what tradeoffs, if any, would result from transforming the data.

The work was carried out over a period of six months with input from a number of interested parties within the development community at Talis and brought together by Rob Styles and Nadeem Shabir.

Described here is how our understanding developed over time from a transliteration of the MARC21 record syntax to a rich semantic description of the many and varied things described by bibliographic records.

5. STRAIGHT-FORWARD REPRESENTATION

An obvious first step is to perform a simple mapping from the MARC format to RDF in much the same way as the text format shown earlier makes a simple human readable form.

Work to do this was done by Davis [5] and this provides a basic and straight-forward representation of MARC in RDF. Davis' work allowed for the record to be reconstructed accurately from the RDF, without that constraint we can produce a very simple transliterated representation of our record. An example of that is shown in figure 3 with some fields removed, the full record is shown in this form in Appendix A.

The root node of this example is the record itself, a blank node in this example. The model, being a transliteration is really no more than the original record transformed syntactically to turtle.

The primary problem with this representation is that the semantics of particular predicates depend on data close-by in the structure, for example the final field, 655, contains "Children's Stories.". That *lcs* is the source of the term, the Library of Congress Subject Headings, is deduced from indicator 2 being "7". This kind of complex interplay with values in indicators establishing the meaning of data in the fields is common throughout the MARC standards.

This representation also suffers from quite severe readability issues for developers, relying on a knowledge of the MARC21 standard to understand the meaning of the data. Ideally we want to go beyond this, so we will look at making the properties more meaningful to humans in the next section. This is key to the semantic nature of the ontology - the simple model above

* <http://www.w3.org/TR/rdf-sparql-query/>

```

@base <http://example.com/a_marc_record> .
@prefix marc21: <http://example.com/marc21#> .
[]
  marc21:LDR "00673nam a2200217 a 4504";
  marc21:001 "9cbb7fc3a7346d99c281979d45b679c";
  marc21:005 "20050705133033.0";
  marc21:008 "990831s1999 enk j 000 ||eng|
d";
  marc21:020 [
    marc21:a "0747542155 :";
  ];
  marc21:100 [
    marc21:ind1 "1";
    marc21:a "Rowling, J. K."
  ];
  marc21:245 [
    marc21:ind1 "0";
    marc21:ind2 "0";
    marc21:a "Harry Potter and the prisoner of
Azkaban /";
    marc21:c "J.K. Rowling."
  ];
  marc21:650 [
    marc21:ind2 "0";
    marc21:a "Potter, Harry (Fictitious
character)";
    marc21:v "Juvenile fiction."
  ], [
    marc21:ind2 "0";
    marc21:a "Wizards";
    marc21:v "Juvenile fiction."
  ];
  marc21:655 [
    marc21:ind2 "7";
    marc21:a "Children's stories.";
    marc21:2 "lcsH"
  ] .

```

Figure 3 - Straight-Forward Representation

provides no semantics over and above the original MARC21 format and, as such, has little value.

The data also contains display punctuation. This is a historic artifact of MARC21 called ISBD punctuation, allowing the data to be concatenated for printing without programmatic formatting. It is widely accepted that this is not ideal. Removing the punctuation requires knowledge of which fields should have specific characters removed from front and back. The Library of Congress has rules for this contained in their MARC to MODS* stylesheets.

6. READABLE REPRESENTATION

The representation above is a very basic transliteration of the MARC standard. The alpha-numeric codes for fields and subfields still dominating. However, the Library Of Congress provide human-readable labels for the field and subfield codes and these are used in some tools to provide a more meaningful representation.

One of the benefits of RDF is the ability to bring data together more effectively than with other formats. Sticking with the

alphanumeric codes alone, all types of MARC would be represented by very similar predicates, differing only in the base URI. While this makes no difference to the machine interpretation of the data it provides difficult and confusing semantics for developers working with the data. By mapping the codes to

```

@base <http://example.com/a_marc_record> .
@prefix marc21: <http://example.com/marc21#> .
[]
  marc21:controlNumber
"9cbb7fc3a7346d99c281979d45b679c";

#Following data comes from fixed positions in the
Leader
  marc21:recordStatus "New";
  marc21:recordType "Language material";
  marc21:bibliographicLevel "Monograph/item";
  marc21:encodingLevel "Full";

#Following data comes from fixed positions in 008
  marc21:recordCreated
"1999-08-31"^^xsd:dateTime;
  marc21:publicationStatus "Published";
  marc21:placeOfPublication "England";
  marc21:language "English";
  marc21:targetAudience "Juvenile";
  marc21:festschrift "No";

#Following data comes from other control fields
  marc21:controlNumberIdentifier "UK-BiTAL";
  marc21:recordUpdated
"2005-07-05T13:30:33Z"^^xsd:dateTime;
  marc21:nationalBibliographyNumber [
    marc21:number "GB99Y5741";
    marc21:sourceOfNumber "bnb";
  ];
  marc21:isbn "0747542155";
  marc21:deweyDecimalClassification "823.914"
  marc21:associatedPersonalName "Rowling, J. K.";
  marc21:title "Harry Potter and the prisoner of
Azkaban";
  marc21:statementOfResponsibility "J.K.
Rowling.";
  marc21:placeOfPublication "London";
  marc21:dateOfPublication "1999"^^xsd:dateTime;
  marc21:publisher "Bloomsbury";
  marc21:physicalExtent "317p.";
  marc21:physicalDimensions "21 cm";
  marc21:topicalTerm [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Potter, Harry (Fictitious
character)";
    marc21:formSubdivision "Juvenile fiction."
  ], [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Wizards";
    marc21:formSubdivision "Juvenile fiction."
  ];
  marc21:genre [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Children's stories."
  ] .

```

Figure 4 - Readable Representation

* <http://www.loc.gov/standards/mods/mods-userguide-intro.html>

bibliographic terms, and other MARC flavors doing the same, it is possible to create a more interoperable ontology - this is what was hoped would happen with MODS [10] and is also the hope for the combined work of DCMI and RDA working groups [4].

Without taking other, existing, schemas into account (at this point) and working with the Library of Congress descriptions we can provide a more semantically rich representation of the data. This involves interpreting the data in certain parts as well as the structure of the record and also requires some fixed format data, such as the Leader and 008 to be parsed.

Doing this, for an incomplete example set from the record above, we arrive at a simpler and more readable record as shown in figure 4. The full record is given in Appendix B.

This more readable representation uses terms we can interpret, apart from 'festschrift' perhaps which may require a lookup*. More importantly, though, the data tied up in fixed positions of fields has been drawn out and the areas where the meaning of a predicate depended on data close-by the predicates have been disambiguated.

An ontology based on the full Library of Congress MARC21 specification would be valuable in its own right, and MODS is very close being just that, as is the full dublicore specification. However, the data still lies in literal values, meaning that each record remains an island of data. The same concepts, such as *Harry Potter*, *London* or *J. K. Rowling* occurring in many records will not be related.




Figure 5 - Visualization of two translated MARC21 records.

A visualization of two translated records, figure 5, shows the problem clearly. What we can see is that each record forms its own island of data. Concepts which we would expect to be shared between records are not shared, leaving little or no opportunity to navigate the data through simple links.

7. LINKS NOT LITERALS

The readable representation provides many benefits, but still fails to exploit the full potential of the data. The use of literals, while it

is syntactically RDF, doesn't give identity to the concepts and doesn't allow them to be referenced. That is, as literals, I can't refer to them in other triples or add additional information about them.

To rectify this we need to replace literal values with URIs representing the concepts that the literals provide names for. This means creating a URI to refer to the resource that we, as people, infer from the literal string. We then use the literal string as a label for the URI.

This is good confirmation of the principles behind the work done at DERI on MarcOnt [12], a similar ontology for MARC21. MarcOnt specifies that subjects should be SKOS concepts and the people involved with a resource should be represented as FOAF person. Other things, such as title, remain string literals.

8. SEMANTIC REPRESENTATION

The URIs used to represent the resources could be arbitrarily assigned using GUIDs or some other mechanism. However, to match the same URI for the same resource would then require a query. As we are processing large volumes of data using a parallel processing architecture we decided to create URIs algorithmically.

If we had assigned URIs rather than computing them then as we parse the data and come across the title *Stardust* we would have to look up the identifier for it, and if there was not one create a new one and register it. This would require a huge number of lookups, a centralized store and distributed locking mechanisms for updates to the store.

Not only did we want to be able to process large volumes of this data in parallel and arrive at the same URIs even when processing data in distributed locations around the net, we also wanted to allow others to process their own data and arrive at a set of URIs that could link in without them having a dependence on us.

To allow for this we have started with a simple hashing algorithm to arrive at a key from a given piece of text. The intention of developing a hash is that different strings that represent the same resource will converge on the same hashed value, while strings representing different resources will diverge on different hashed values.

The algorithm is currently the same for names, titles, subjects and other types of text. We feel confident that there are opportunities to develop optimized algorithms for names and subject terms. This could allow a higher degree of accuracy in matching texts that represent the same concept.

Our initial algorithm was formulated on data mostly in English with a few entries in other Western European languages. Different techniques would be required for different language groups.

Our starting point is to remove all punctuation and whitespace and lower-case the string. When appended to a base URI for each type of datum this gives a simple URI that will be consistent for the main variations that occur in bibliographic data.

* <http://en.wikipedia.org/wiki/Festschrift>

15. OTHER ONTOLOGIES

The work described in this paper focussed on understanding what was possible with MARC21 data rather than broader interoperability issues. Next stages under consideration by the team are to compare and contrast the ontology resulting from this work with other efforts such as MarcOnt, Bibliontology* and the RDF Book Mashup.

The team maintain a watching brief on the work being done by DCMI and RDA working groups and the work being done by the Library of Congress and other organizations such as the Internet Archive's Open Library project.

16. SUMMARY

The work done here provides the start of an approach that would allow decades of interesting and culturally valuable data to be transformed into a part of the web of data.

Further research is needed to arrive at hashing algorithms that maximize the matching of resources from literals strings and the teams is interested in hearing suggestions on that.

It is the team's hope to release a substantial set of data onto the web using these approaches during 2008 at which time the team will be looking to link both to other data sets and other ontologies.

17. REFERENCES

- [1] Auer, S., Bizer, C., Lehmann, J., Kobilarov, G., Cyganiak, R. and Ives, Z. (2007) DBpedia: A Nucleus for a Web of Open Data. In 6th International Semantic Web Conference, Busan, Korea.
- [2] Bizer C., Cyganiak R., Gauß T. (007) The RDF Book Mashup: From Web APIs to a Web of Data <http://sites.wiwiss.fu-berlin.de/suhl/bizer/pub/Bizer-ESWC2007-RDFbookmashup.pdf>
- [3] Bizer C., Heath T., Ayers D., Raimond Y. (2007) Interlinking Open Data on the Web. In Demonstrations Track, 4th European Semantic Web Conference (ESWC2007), Innsbruck, Austria. <http://www.eswc2007.org/pdf/demo-pdf/LinkingOpenData.pdf>
- [4] Clayphan R. et al (2007) Data Model Meeting <http://www.bl.uk/services/bibliographic/meeting.html>
- [5] Davis I. (2005) MARC Transliteration <http://iandavis.com/blog/2005/12/marc-transliteration>
- [6] Delsey T. (2002) Functional Analysis of the MARC 21 Bibliographic and Holdings Formats <http://www.loc.gov/marc/marc-functional-analysis/functional-analysis.html>
- [7] Hickey T., O'Neill E., Toves J. (2002) Experiments with the IFLA Functional Requirements for Bibliographic Records (FRBR) <http://www.dlib.org/dlib/september02/hickey/09hickey.html>
- [8] Furrie, B. (2003) Understanding MARC Bibliographic: Machine-Readable Cataloging <http://www.loc.gov/marc/umb/>
- [9] Madison O. et al (2008) On The Record: Report of The Library of Congress Working Group on the Future of Bibliographic Control <http://www.loc.gov/bibliographic-future/news/lcwg-ontherecord-jan08-final.pdf>
- [10] Moen W. (2005) Metadata Interaction, Integration, and Interoperability http://www.unt.edu/wmoen/presentations/MD_Interoperability_wem_June2005.ppt
- [11] Soler J. (2007) Separating the articles of authors with the same name DOI=10.1007/s11192-007-1730-z
- [12] Synak M., Kruk S. R. (2005) MarcOnt Initiative - the Ontology for the Librarian World http://www.marcont.org/marcont/pdf/ms_eswc2005marcont.pdf
- [13] Yee M., (2005) FRBRization: a Method for Turning Online Public Finding Lists into Online Public Catalogs <http://repositories.cdlib.org/postprints/715>

* <http://bibliontology.com/>

APPENDIX A - STRAIGHT-FORWARD REPRESENTATION

```
@base <http://example.com/a_marc_record> .
@prefix marc21: <http://example.com/marc21#> .
[
  marc21:LDR "00673nam a2200217 a 4504";
  marc21:001 "9cbbe7fc3a7346d99c281979d45b679c";
  marc21:003 "UK-BiTAL";
  marc21:005 "20050705133033.0";
  marc21:008 "990831s1999 enk j 000 ||eng|d";
  marc21:015 [
    marc21:a "GB99Y5741";
    marc21:2 "bnb"
  ];
  marc21:020 [
    marc21:a "0747542155 :";
  ];
  marc21:035 [
    marc21:a "()0747542155";
  ];
  marc21:040 [
    marc21:a "StDuBDS";
    marc21:c "StDuBDS";
    marc21:d "UK-BiTAL"
  ];
  marc21:082> [
    marc21:ind1 "0";
    marc21:ind2 "4";
    marc21:a "823.914$221";
  ];
  marc21:100 [
    marc21:ind1 "1";
    marc21:a "Rowling, J. K.";
  ];
  marc21:245> [
    marc21:ind1 "0";
    marc21:ind2 "0";
    marc21:a "Harry Potter and the prisoner of Azkaban /";
    marc21:c "J.K. Rowling.";
  ];
  marc21:260 [
    marc21:a "London :";
    marc21:b "Bloomsbury, ";
    marc21:c "1999.";
  ];
  marc21:300 [
    marc21:a "317p. ";
    marc21:c "21 cm.";
  ];
  marc21:650 [
    marc21:ind2 "0";
    marc21:a "Potter, Harry (Fictitious character)";
    marc21:v "Juvenile fiction."
  ], [
    marc21:ind2 "0";
    marc21:a "Wizards";
    marc21:v "Juvenile fiction."
  ];
  marc21:655 [
    marc21:ind2 "7";
    marc21:a "Children's stories.";
    marc21:2 "lcsh"
  ]
] .
```

APPENDIX B - READABLE REPRESENTATION

```
@base <http://example.com/a_marc_record> .
@prefix marc21: <http://example.com/marc21#> .
[]
  marc21:controlNumber "9cbbe7fc3a7346d99c281979d45b679c";

  #Following data comes from fixed positions in the Leader
  marc21:recordStatus "New";
  marc21:recordType "Language material";
  marc21:bibliographicLevel "Monograph/item";
  marc21:encodingLevel "Full";

  #Following data comes from fixed positions in 008
  marc21:recordCreated "1999-08-31"^^xsd:dateTime;
  marc21:publicationStatus "Published";
  marc21:placeOfPublication "England";
  marc21:language "English";
  marc21:targetAudience "Juvenile";
  marc21:festschrift "No";

  #Following data comes from other control fields
  marc21:controlNumberIdentifier "UK-BiTAL";
  marc21:recordUpdated "2005-07-05T13:30:33Z"^^xsd:dateTime;
  marc21:nationalBibliographyNumber [
    marc21:number "GB99Y5741";
    marc21:sourceOfNumber "bnb";
  ];
  marc21:isbn "0747542155";
  marc21:deweyDecimalClassification "823.914"
  marc21:associatedPersonalName "Rowling, J. K.";
  marc21:title "Harry Potter and the prisoner of Azkaban";
  marc21:statementOfResponsibility "J.K. Rowling.";
  marc21:placeOfPublication "London";
  marc21:dateOfPublication "1999"^^xsd:dateTime;
  marc21:publisher "Bloomsbury";
  marc21:physicalExtent "317p.";
  marc21:physicalDimensions "21 cm";
  marc21:topicalTerm [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Potter, Harry (Fictitious character)";
    marc21:formSubdivision "Juvenile fiction.";
  ], [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Wizards";
    marc21:formSubdivision "Juvenile fiction."
  ];
  marc21:genre [
    marc21:sourceOfTerm "LCSH";
    marc21:term "Children's stories.";
  ] .
```

APPENDIX C - SEMANTIC REPRESENTATION

```
@base <http://example.com/potter.rdf> .
@prefix rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#> .
@prefix bib: <http://example.com/schema/bib#> .
@prefix frbr: <http://purl.org/vocab/frbr/core#> .

<http://example.com/resources/people/rowlingjk#self>
  bib:writesAbout <http://example.com/resources/genres/childrensstories#self>, <http://example.com/
resources/topics/wizards#self>, <http://example.com/resources/topics/
potterharryfictitiouscharacter#self> ;
  bib:publisher <http://example.com/resources/organizations/bloomsbury#self> ;
  frbr:creatorOf <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self>,
<http://example.com/resources/expressions/7a67d02fe5b1f4fcc78eb91135a7d0#self>, <http://example.com/
resources/works/d415d3e7bb88725134eb21d11718bdaa#self> ;
  bib:seenAs "Rowling, J. K." ;
  a bib:Person ;
  frbr:creatorOf <http://example.com/resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self>,
<http://example.com/resources/expressions/7df5817e8c75b34766169d8ade554bfe#self>, <http://example.com/
resources/works/7317d9412ec8b84e0bfe9989d1521#self> .

<http://example.com/resources/organizations/bloomsbury#self>
  bib:publisherOf <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self>,
<http://example.com/resources/people/rowlingjk#self> ;
  bib:seenAs "Bloomsbury," ;
  a bib:Publisher ;
  bib:publisherOf <http://example.com/resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self> .

<http://example.com/resources/expressions/7a67d02fe5b1f4fcc78eb91135a7d0#self>
  bib:format <http://example.com/resources/languages/eng#self>, <http://example.com/resources/formats/
a#self> ;
  bib:isbn <http://example.com/resources/isbns/9780747542155#self> ;
  bib:name <http://example.com/resources/titles/harrypotterandtheprisonerofazkaban#self> ;
  frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
  frbr:embodiment <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self> ;
  frbr:realizationOf <http://example.com/resources/works/d415d3e7bb88725134eb21d11718bdaa#self> ;
  a frbr:Expression .

<http://example.com/resources/titles/harrypotterandtheprisonerofazkaban#self>
  bib:nameOf <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self>, <http://
example.com/resources/expressions/7a67d02fe5b1f4fcc78eb91135a7d0#self>, <http://example.com/resources/
works/d415d3e7bb88725134eb21d11718bdaa#self> ;
  bib:seenAs "Harry Potter and the prisoner of Azkaban /" ;
  a bib:Title .

<http://example.com/resources/dates/1999#self>
  a bib:Date .

<http://example.com/resources/languages/eng#self>
  a bib:Language .

<http://example.com/resources/works/d415d3e7bb88725134eb21d11718bdaa#self>
  frbr:subject <http://example.com/resources/genres/childrensstories#self>, <http://example.com/
resources/topics/wizards#self>, <http://example.com/resources/topics/
potterharryfictitiouscharacter#self> ;
  bib:isbn <http://example.com/resources/isbns/9780747542155#self> ;
  bib:name <http://example.com/resources/titles/harrypotterandtheprisonerofazkaban#self> ;
  frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
  <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self> <http://example.com/
resources/expressions/7a67d02fe5b1f4fcc78eb91135a7d0#self> ;
  a frbr:Work .

<http://example.com/resources/genres/childrensstories#self>
  bib:seenAs "Children's stories." ;
  a bib:Genre .

<http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self>
  bib:format <http://example.com/resources/languages/eng#self>, <http://example.com/resources/formats/
a#self> ;
  bib:datePublished <http://example.com/resources/dates/1999#self> ;
  bib:publisher <http://example.com/resources/organizations/bloomsbury#self> ;
```

```

bib:isbn <http://example.com/resources/isbns/9780747542155#self> ;
bib:name <http://example.com/resources/titles/harrypotterandtheprisonerofazkaban#self> ;
frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
frbr:embodimentOf <http://example.com/resources/expressions/7a67d02fe5b1f4fcc78eb91135a7d0#self> ;
a frbr:Manifestation .

<http://example.com/resources/formats/a#self>
  a bib:Format .

<http://example.com/resources/topics/potterharryfictitiouscharacter#self>
  bib:seenAs "Potter, Harry (Fictitious character)" ;
  a bib:Topic .

<http://example.com/resources/isbns/0747542155#self>
  bib:seeAlso <http://example.com/resources/isbns/9780747542155#self> ;
  bib:seenAs "0747542155" ;
  a bib:ISBN .

<http://example.com/resources/isbns/9780747542155#self>
  <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self> <http://example.com/
resources/manifestations/988e45a216923b3d24e4a4a711a664#self>, <http://example.com/resources/expressions/
7a67d02fe5b1f4fcc78eb91135a7d0#self>, <http://example.com/resources/works/
d415d3e7bb88725134eb21d11718bdaa#self> ;
  bib:seeAlso <http://example.com/resources/isbns/0747542155#self> ;
  bib:seenAs "9780747542155" ;
  a bib:ISBN .

<http://example.com/resources/topics/wizards#self>
  bib:seenAs "Wizards" ;
  a bib:Topic .

<http://example.com/resources/expressions/7df5817e8c75b34766169d8ade554bfe#self>
  bib:format <http://example.com/resources/languages/eng#self>, <http://example.com/resources/formats/
a#self> ;
  bib:isbn <http://example.com/resources/isbns/9780747538493#self> ;
  bib:name <http://example.com/resources/titles/harrypotterandthechamberofsecrets#self> ;
  frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
  frbr:embodiment <http://example.com/resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self> ;
  frbr:realizationOf <http://example.com/resources/works/7317d9412ec8b84e0bfe9989d1521#self> ;
  a frbr:Expression .

<http://example.com/resources/isbns/0747538492#self>
  bib:seeAlso <http://example.com/resources/isbns/9780747538493#self> ;
  bib:seenAs "0747538492" ;
  a bib:ISBN .

<http://example.com/resources/works/7317d9412ec8b84e0bfe9989d1521#self>
  frbr:subject <http://example.com/resources/genres/childrensstories#self>, <http://example.com/
resources/topics/wizards#self> ;
  bib:isbn <http://example.com/resources/isbns/9780747538493#self> ;
  bib:name <http://example.com/resources/titles/harrypotterandthechamberofsecrets#self> ;
  frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
  <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self> <http://example.com/
resources/expressions/7df5817e8c75b34766169d8ade554bfe#self> ;
  a frbr:Work .

<http://example.com/resources/isbns/9780747538493#self>
  <http://example.com/resources/manifestations/988e45a216923b3d24e4a4a711a664#self> <http://example.com/
resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self>, <http://example.com/resources/expressions/
7df5817e8c75b34766169d8ade554bfe#self>, <http://example.com/resources/works/
7317d9412ec8b84e0bfe9989d1521#self> ;
  bib:seeAlso <http://example.com/resources/isbns/0747538492#self> ;
  bib:seenAs "9780747538493" ;
  a bib:ISBN .

<http://example.com/resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self>
  bib:format <http://example.com/resources/languages/eng#self>, <http://example.com/resources/formats/
a#self> ;
  bib:datePublished <http://example.com/resources/dates/1998#self> ;
  bib:publisher <http://example.com/resources/organizations/bloomsbury#self> ;
  bib:isbn <http://example.com/resources/isbns/9780747538493#self> ;
  bib:name <http://example.com/resources/titles/harrypotterandthechamberofsecrets#self> ;
```

```
frbr:creator <http://example.com/resources/people/rowlingjk#self> ;
frbr:embodimentOf <http://example.com/resources/expressions/7df5817e8c75b34766169d8ade554bfe#self> ;
a frbr:Manifestation .

<http://example.com/resources/titles/harrypotterandthechamberofsecrets#self>
  bib:nameOf <http://example.com/resources/manifestations/62c544b579c57dd1c1e4092d0d02a1#self>, <http://
example.com/resources/expressions/7df5817e8c75b34766169d8ade554bfe#self>, <http://example.com/resources/
works/7317d9412ec8b84e0bfe9989d1521#self> ;
  bib:seenAs "Harry Potter and the chamber of secrets /" ;
  a bib:Title .

<http://example.com/resources/dates/1998#self>
  a bib:Date .
```