


Acrylamide

CAS No. 79-06-1

Reasonably anticipated to be a human carcinogen
First Listed in the *Sixth Annual Report on Carcinogens* (1991)



Carcinogenicity

Acrylamide is *reasonably anticipated to be a human carcinogen* based on sufficient evidence of carcinogenicity in experimental animals (IARC 1986, 1987, 1994). When administered in the drinking water, acrylamide increased the incidences of adrenal pheochromocytomas and mesotheliomas of the tunica of the testes in male rats; pituitary adenomas, mammary adenomas and adenocarcinomas, oral cavity papillomas, uterine adenocarcinomas, and clitoral gland adenomas in female rats; and follicular adenomas of the thyroid in rats of both sexes. When administered by gavage or by intraperitoneal injection, acrylamide increased both the incidence and multiplicity of lung adenomas in mice of both sexes. When administered topically, by gavage, or by intraperitoneal injection followed by long-term topical treatment with 12-*o*-tetradecanoylphorbol-13-acetate, acrylamide induced skin squamous cell papillomas and squamous cell carcinomas in female mice.

No adequate data were available to evaluate the carcinogenicity of acrylamide in humans (IARC 1986, 1987, 1994).

Properties

Acrylamide occurs in crystalline form and in aqueous solution. The solid monomer is a colorless to white, free-flowing crystal that is soluble in water, methanol, ethanol, dimethyl ether, and acetone, and is insoluble in benzene and heptane. It melts at 84 to 85°C and boils at 125°C. The crystalline acrylamide monomer is available as pellets of 98% and 95% purity. The 50% aqueous form is the preferred form for applications in which water can be tolerated. The monomer readily polymerizes at the melting point or under ultraviolet light. Solid acrylamide is stable at room temperature, but it may polymerize violently when melted or in contact with oxidizing agents. When heated to decomposition, acrylamide emits acrid fumes and nitrogen oxides. Commercial acrylamide monomer contains residual levels of acrylonitrile (1 to 100 mg/kg) (IARC 1986). Residual acrylamide monomer is present in the polymer at approximately 0.01% (Fujiki *et al.* 1985, IARC 1986).

Use

Acrylamide is a chemical intermediate used in the production and synthesis of polyacrylamides (IARC 1986, 1994). These high-molecular weight polymers can be modified to develop nonionic, anionic, or cationic properties for specific uses. The principle end use of acrylamide is in water-soluble polymers used as additives for water treatment, enhanced oil recovery, flocculants, papermaking aids, thickeners, soil conditioning agents, sewage and waste treatment, ore processing, and permanent-press fabrics (Kirk-Othmer 1978, Sax and Lewis 1987). Acrylamide is also used in the synthesis of dyes, in copolymers for contact lenses, and the construction of dam foundations, tunnels, and sewers (Kirk-Othmer 1979).

The largest use for polyacrylamide is in treating municipal drinking water and waste water (IARC 1986). The polymer is also used to remove suspended solids from industrial waste water before discharge, reuse, or disposal. Polyacrylamide used for potable water should not contain more than 0.05% residual monomer (Kirk-Othmer 1978). The polymers bind with particles and form heavy aggregates that rapidly settle out of solution and leave a clear supernatant (IARC 1986). Ten to thirty

percent of the annual production volume is used in oil-recovery processes in which the polyacrylamides increase water viscosity. Acrylamides also find use in oil-drilling processes to control fluid losses. In the pulp and paper industry, polyacrylamides are used as binders and retention aids for fibers and to retain pigments on paper fibers. The paper industry uses approximately 20% of the annual U.S. production volume. Polyacrylamides are used to clarify waste water, recover tailings, and flocculate ores in mineral processing. They are incorporated in cement to slow the dehydration process to improve structural strength. Methylated polyacrylamide with subsequent radiation curing is used to produce waterproof concrete. Acrylamide is a soil stabilizer and also finds use in foundry operations to facilitate free sand flow into molds. Polyacrylamides are incorporated in coatings as dispersants and binders and in water-based paints for pigment suspension and flow. Home appliances, building materials, and automotive parts are coated with acrylamide resins and thermosetting acrylics. Acrylamides are formulated in cosmetics and soap preparations as thickeners and in dental fixtures, hair grooming preparations, and preshave lotions. In the textile industry, polyacrylamides are used to size and shrink-proof material and as water repellents. Minor uses of acrylamide are as latex thickeners, emulsion stabilizers for printing inks, gelling agents for explosives, binders in adhesives and adhesive tape; in the production of diazo compounds; and for gel chromatography and electrophoresis (Sittig 1985, IARC 1986). When added to herbicidal gels, polyacrylamides restrict herbicidal treatment to the bottom of lakes or reservoirs by allowing the herbicides to sink before they disperse. The FDA has regulated the use of acrylamide and polyacrylamide in foods. Up to 10 mg polyacrylamide/L water can be used to wash or peel fruits and vegetables; acrylamide monomer should not exceed 0.2%. Acrylamide resins may be added to water for steam that will contact food; the monomer should not exceed 0.05% by weight. Polyacrylamide may be used in gelatin capsules if no more than 0.2% of the monomer is present. Acrylamide polymers may be used in food packaging adhesives, and acrylamide resins, containing <0.2% monomer, may be used in food packaging paper and paperboard if the resin is ≤2% of the weight of the paper.

Production

Currently, 33 U.S. suppliers of acrylamide are listed by Chem Sources (2001). The 1998 *Chemical Buyers Directory* named nine such companies (Tilton 1997). The 1997 *Directory of Chemical Producers* listed four producers of the compound, with a total output of 217 million lb (SRI 1997). Two U.S. manufacturers of acrylamide monomer were identified for 1994, but no production values were provided (USITC 1995). In 1992, three manufacturers were reported to produce 113.5 million lb of the chemical (USITC 1994). Two producers for acrylamide monomer were listed by USITC (1991, 1993) for 1990 and 1991, and three producers for 1988 (USITC 1989), without any production figures. Four U.S. producers reportedly manufactured 47.1 million lb in 1986 (USITC 1987), and an estimated 70 million lb was produced in 1974 (Sittig 1985).

For 1992, U.S. imports totaled 15 million lb and exports were estimated to be less than 2 million lb (EPA 1994). Twenty years earlier, the volumes were considered negligible (HSDB 2000).

Exposure

Acrylamide can be absorbed through unbroken skin, mucous membranes and lungs, and the gastrointestinal tract (Klaassen *et al.* 1986, Merck 1989). NIOSH estimates that approximately 20,000 workers were potentially exposed to acrylamide in 1976 (IARC 1986). Human exposure to acrylamide is primarily occupational from dermal contact with the solid monomer and inhalation of dust and vapor (Kirk-Othmer 1978, Howard 1989). Occupational exposure to the aqueous form is primarily confined to maintenance and repair operations and connection and disconnection for transport. Routine exposure is minimal for captive

operations. Polymerized acrylamide is not toxic, but the monomer can cause peripheral neuropathy (Klaassen *et al.* 1986). Residual monomer in the polymers is a concern (Howard 1989). Improvements in the polymerization process have reduced the monomer content of the nonpotable water-grade polymers from 5% to 0.3% (Brown *et al.* 1982).

Workers in the paper and pulp, construction, foundry, oil drilling, textiles, cosmetics, food processing, plastics, mining, and agricultural industries are potentially exposed to acrylamide. Although exposure levels have not been reported for grouters, the potential exposure for these personnel may be greater than for other workers because of the uncontrolled nature of the exposure (WHO 1985). The National Occupational Health Survey (1972-1974) estimated that 10,368 workers were exposed to acrylamide (Howard 1989). The National Occupational Exposure Survey (1981-1983) estimated that 9,776 workers potentially were exposed (NIOSH 1984). This estimate was based on observations of actual use of the chemical (43%) and as an ingredient of trade name products (57%).

Primary exposure occurs during the handling of the monomer. Two acrylamide manufacturing plants showed breathing zone concentrations of 0.1 to 3.6 mg/m³ (IARC 1986). During normal operations, workers at another plant were exposed to not more than 0.3 mg/m³.

Although human exposure to acrylamide is primarily occupational, the general public may be exposed through consumption of certain foods in their diet (Tareke *et al.* 2002). Acrylamide is formed during heating of starch-rich foods to high temperatures. Studies with laboratory-heated foods revealed a temperature dependence of acrylamide formation. Moderate levels of acrylamide (5-50 mg/kg) were measured in heated protein-rich foods and higher contents (150-4000 mg/kg) in carbohydrate-rich foods, such as potato, beetroot, and also certain heated commercial potato products and crispbread. Acrylamide could not be detected in unheated control or boiled foods (< 5 mg/kg). Consumption habits indicate that the acrylamide levels in the studied heated foods could lead to a daily intake of a few tens of micrograms (Tareke *et al.* 2002).

Another source of exposure of the general public to acrylamide could be through contaminated drinking water from polyacrylamide flocculants used in water treatment (Brown *et al.* 1980a, Howard 1989). Residual acrylamide concentrations in 32 polyacrylamide flocculants approved for water treatment plants ranged from 0.5 to 600 ppm (Howard 1989). Acrylamide may not be removed in many water treatment processes (Croll *et al.* 1974). Acrylamide remains in water after flocculation with polyacrylamides because it is very water soluble and is not readily adsorbed by sediment (Brown *et al.* 1980b). Acrylamide and polyacrylamides are used in the manufacture of a number of consumer products, including textiles, contact lenses, appliances, building materials, cosmetic and soap preparations, food, and gelatin capsules (Kirk-Othmer 1979).

Acrylamide may be released into the environment from waste during acrylamide production and the manufacture of polyacrylamides and other polymers (Howard 1989). Release to water also occurs from acrylamide-based sewer grouting and wastepaper recycling (Brown *et al.* 1980b, 1982, Howard 1989). The most important environmental contamination results from the use of acrylamide in soil grouting (WHO 1985). Acrylamide biodegrades in water in approximately 8 to 12 days (Howard 1989). Acrylamide may not be completely degraded in sewage works and water treatment facilities if residence times are relatively short (Brown *et al.* 1982, Howard 1989). Acrylamide degradation in a secondary sewage plant would be complete in approximately 10 days (Kirk-Othmer 1978). It has been detected in effluent from a sewage treatment plant. Adsorption to sediment and volatilization is not appreciable. Certain debris organisms that exist in anaerobic, light aerobic, or dark aerobic conditions in natural and polluted environments are able to degrade acrylamide (Brown *et al.* 1980b). Bacteriologic degradation will likely depend on temperature fluctuations in temperate climates. Although acrylamide is highly

mobile in aqueous environments, readily leaches into soil, and is carried great distances in ground water of deep rock aquifers where biodegradability is reportedly absent (WHO 1985), bioconcentration of acrylamide is unlikely because it degrades easily in surface waters and is highly water soluble (Kirk-Othmer 1978). In an EPA study of five industrial sites (beyond plant site perimeters) of acrylamide and polyacrylamide producers and one polyacrylamide user, acrylamide (1.5 ppm) was found in only one sample downstream from a polyacrylamide producer; no acrylamide was detected in soil or air samples (WHO 1985, Howard 1989). An average acrylamide concentration in air was <0.2 µg/m³ near six acrylamide or polyacrylamide plants. The vapor pressure of acrylamide is low, and the monomer is not expected to be distributed in the atmosphere (WHO 1985).

Environmental contamination may result from disposal on land or from leaching of the residual monomer from polyacrylamides. The Toxic Chemical Release Inventory (TRI) estimated that 5,912,663 lb of acrylamide were released to the environment from 43 facilities that produced, processed, or used the chemical in the United States in 1996 (TRI96 1998). That number increased to 7,542,385 lb from 90 facilities in 1999. Of that total, 99.6% was released to underground injection. Forty-four facilities were responsible for the 24,874 lb of acrylamide emitted to air. Twenty-one facilities, each releasing >100 lb to air, represented 98.7% of the total emission; one facility located in Greensboro, North Carolina, reporting under industrial classifications for chemical preparations, NEC (SIC Code 2899), and releasing >9,000 lb of acrylamide, accounted for 39.8% of total air releases. Other 1999 total releases were 370 lb to water and 6,289 lb to land (TRI99 2001).

Regulations

DOT

Acrylamide is considered a hazardous material and special requirements have been set for marking, labeling, and transporting this material

EPA

Clean Air Act

NESHAP: Listed as a Hazardous Air Pollutant (HAP)

NSPS: Manufacture of substance is subject to certain provisions for the control of Volatile Organic Compound (VOC) emissions

Comprehensive Environmental Response Compensation and Liability Act

Reportable Quantity (RQ) = 5,000 lb

Emergency Planning and Community Right-to-Know Act

Toxics Release Inventory: Listed substance subject to reporting requirements

Reportable Quantity (RQ) = 5,000 lb

Threshold Planning Quantity (TPQ) = 1,000 lb (solids in powder form particle size <100 microns, or solution or molten form); 10,000 lb (all other forms)

Resource Conservation and Recovery Act

Listed Hazardous Waste: Waste codes in which listing is based wholly or partly on substance - U007,K014

Listed as a Hazardous Constituent of Waste

Safe Drinking Water Act

Treatment Technique: 0.05% - dosed at 1 mg/L (or equivalent) in drinking water systems

FDA

Acrylamide may be used in polymers for adhesives, coatings, paperboard packaging, and plastics that are in contact with food and may be used in treating food with maximum residual acrylamide monomer levels ranging from 0.05-0.20%

Acrylamide may be used in animal feeds as a thickener provided residual acrylamide levels do not exceed 0.05%

OSHA

Permissible Exposure Limit (PEL) = 0.3 mg/m³

Guidelines

ACGIH

Threshold Limit Value - Time-Weighted Average Limit (TLV-TWA) = 0.03 mg/m³

NIOSH

Immediately Dangerous to Life and Health (IDLH) = 60 mg/m³

Recommended Exposure Limit (time-weighted-average workday) = 0.03 mg/m³

Listed as a potential occupational carcinogen

REFERENCES

Brown, L., M. M. Rhead, K. C. C. Bancroft and N. Allen. 1980a. Case studies of acrylamide pollution resulting from industrial use of acrylamides. *Water Pollut Control* 79(4): 507-510.

SUBSTANCE PROFILES

- Brown, L., M. M. Rhead, K. C. C. Bancroft and N. Allen. 1980b. Model studies of the degradation of acrylamide monomer. *Water Res* 14(7): 775-778.
- Brown, L., M. M. Rhead, D. Hill and K. C. C. Bancroft. 1982. Rapid screening technique utilizing high-performance liquid chromatography for assessing acrylamide contamination in effluents. *Analyst* 107(1276): 749-754.
- ChemSources. 2001. Chemical Sources International, Inc. <http://www.chemsources.com>.
- Croll, B. T., G. M. Arkell and R. P. J. Hodge. 1974. Residues of acrylamide in water. *Water Res* 8: 989-993.
- EPA. 1994. Chemical Summary for Acrylamide. U.S. Environmental Protection Agency, Office of Pollution Prevention and Toxics. http://www.epa.gov/opptintr/chemfact/s_acryla.txt.
- Fujiki, M., J. Asada and T. Shimizu. 1985. Studies on Analytical Method of Acrylamide Monomer and Accumulation into Fish. Govt Reports Announcements and Index (21).
- Howard, P. H. 1989. Handbook of Environmental Fate and Exposure Data for Organic Chemicals., vol 1, Large Production and Priority Pollutants. Chelsea, MI: Lewis Publishers. p. 13-19.
- HSDB. 2000. Hazardous Substances Data Base. National Library of Medicine. <http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB>.
- IARC. 1986. Some Chemicals Used in Plastics and Elastomers. IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Humans, vol. 39. Lyon, France: International Agency for Research on Cancer. 403 pp.
- IARC. 1987. Overall Evaluations of Carcinogenicity. IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Humans, Supplement 7. Lyon, France: International Agency for Research on Cancer. 440 pp.
- IARC. 1994. Some Industrial Chemicals. IARC Monographs on the Evaluation of Carcinogenic Risk of Chemicals to Humans, vol. 60. Lyon, France: International Agency for Research on Cancer. 560 pp.
- Kirk-Othmer. 1978. Kirk-Othmer Encyclopedia of Chemical Technology, 3rd ed., vol. 1. New York, NY: John Wiley and Sons.
- Kirk-Othmer. 1979. Kirk-Othmer Encyclopedia of Chemical Technology, 3rd ed., vol. 6. New York, NY: John Wiley and Sons.
- Klaasen, C., A. M. and J. Doull. 1986. Casaret and Doull's Toxicology: The Basic Science of Poisons. New York, NY: Macmillan.
- Merck. 1989. The Merck Index, 11th ed. Rahway, NJ: Merck & Company, Inc.
- NIOSH. 1984. National Occupational Exposure Survey (1981-83). Cincinnati, OH: U. S. Department of Health and Human Services. <http://www.cdc.gov/noes/noes3/empl0003.html>.
- Sax, N. I. and R. J. Lewis. 1987. Hawley's Condensed Chemical Dictionary, 11th ed. New York: Van Nostrand Reinhold Co.
- Sittig, M. 1985. Handbook of Toxic and Hazardous Chemicals and Carcinogens, 2nd ed. Park Ridge, NJ: Noyes Publications. 950 pp.
- SRI. 1997. Directory of Chemical Producers, United States, 1997. Stanford Research Institute, Menlo Park, CA: SRI International.
- Tareke, E., Rydberg, P., Karlsson, P., Eriksson, S., and M. Törnqvist 2002. Analysis of acrylamide, a carcinogen formed in heated foodstuffs. *J Agric Food Chem* 50(17): 4998-5006.
- Tilton, H., ed. 1997. OPD Chemical Buyers Directory 1998. The Green Book. 85th ed. New York, NY, Schnell Publishing.
- TRI96. 1998. Toxic Chemical Release Inventory 1996. Data contained in the Toxic Chemical Release Inventory (TRI). National Library of Medicine.
- TRI99. 2001. Toxic Chemical Release Inventory 1999. Data contained in the Toxic Chemical Release Inventory (TRI). National Library of Medicine. <http://www.epa.gov/triexplorer/>.
- USITC. 1987. Synthetic Organic Chemicals, United States Production and Sales, 1986. USITC Publication No 2009. Washington, D.C.: U.S. Government Printing Office.
- USITC. 1989. Synthetic Organic Chemicals, United States Production and Sales, 1988. USITC Publication No 2219. Washington, D.C.: U.S. Government Printing Office.
- USITC. 1991. Synthetic Organic Chemicals, United States Production and Sales, 1990. USITC Publication No 2470. Washington, D.C.: U.S. Government Printing Office.
- USITC. 1993. Synthetic Organic Chemicals, United States Production and Sales, 1991. USITC Publication No 2607. Washington, D.C.: U.S. Government Printing Office.
- USITC. 1994. Synthetic Organic Chemicals, United States Production and Sales, 1992. USITC Publication No 2720. Washington, D.C.: U.S. Government Printing Office.
- USITC. 1995. Synthetic Organic Chemicals, United States Production and Sales, 1994. USITC Publication No 2933. Washington, D.C.: U.S. Government Printing Office.
- WHO. 1985. Acrylamide. Environmental Health Criteria 49. Geneva: World Health Organization. 121 pp.
-