

HTTP/1.1 200 OK  
Date: Tue, 09 Apr 2002 06:00:00 GMT  
Server: Apache/1.3.20 (Unix)  
Last-Modified: Mon, 14 Feb 2000 14:04:00 GMT  
ETag: "2e64cb-5c01-38a80b50"  
Accept-Ranges: bytes  
Content-Length: 23553  
Connection: close  
Content-Type: text/plain

OpenPGP Working Group  
draft-ietf-openpgp-mime-00.txt  
Obsoletes: 2015

M. Elkins  
Network Associates, Inc.  
D. Del Torto  
CryptoRights Foundation  
R. Levien  
University of California at Berkeley  
T. Roessler  
February 2000

## MIME Security with OpenPGP

### Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of Section 10 of RFC2026.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Copyright (C) The Internet Society 2000. All Rights Reserved.

### Abstract

This document describes how the OpenPGP Message Format [1] can be used to provide privacy and authentication using the Multipurpose Internet Mail Extensions (MIME) security content types described in RFC1847 [2].

This draft is being discussed on the "ietf-openpgp" mailing list. To join the list, send a message to <[ietf-openpgp-request@imc.org](mailto:ietf-openpgp-request@imc.org)> with the single word "subscribe" in the subject. A web site containing an archive of the list can be found at <<http://www.imc.org/ietf-openpgp>>.

## 1. Introduction

Work on integrating PGP (Pretty Good Privacy) with MIME [3] (including the since withdrawn application/pgp content type) prior to RFC 2015 suffered from a number of problems, the most significant of which is the inability to recover signed message bodies without parsing data structures specific to PGP. RFC 2015 makes use of the elegant solution proposed in RFC1847, which defines security multipart formats for MIME. The security multiparts clearly separate the signed message body from the signature, and have a number of other desirable properties. This document revises RFC 2015 to adopt the integration of PGP and MIME to the needs which emerged during the work on the OpenPGP specification.

This document defines three content types for implementing security and privacy with OpenPGP: application/pgp-encrypted, application/pgp-signature and application/pgp-keys.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119.

## 2. OpenPGP data formats

OpenPGP implementations can generate either ASCII armor (described in [1]) or 8-bit binary output when encrypting data, generating a digital signature, or extracting public key data. The ASCII armor output is the REQUIRED method for data transfer. This allows those users who do not have the means to interpret the formats described in this document to be able extract and use the OpenPGP information in the message.

When the amount of data to be transmitted requires that it be sent in many parts, the MIME message/partial mechanism SHOULD be used rather than the multipart ASCII armor OpenPGP format.

## 3. Content-Transfer-Encoding restrictions

Multipart/signed and multipart/encrypted are to be treated by agents as opaque, meaning that the data is not to be altered in any way [2], [7]. However, many existing mail gateways will detect if the next hop does not support MIME or 8-bit data and perform conversion to either Quoted-Printable or Base64. This presents serious problems for multipart/signed, in particular, where the signature is invalidated when such an operation occurs. For this reason all data signed according to this protocol MUST be constrained to 7 bits (8-bit data MUST be encoded using either Quoted-Printable or Base64). Note that

this also includes the case where a signed object is also encrypted (see section 6). This restriction will increase the likelihood that the signature will be valid upon receipt.

Data that is ONLY to be encrypted is allowed to contain 8-bit characters and therefore need not be converted to a 7-bit format.

Implementor's note: It cannot be stressed enough that applications using this standard follow MIME's suggestion that you "be conservative in what you generate, and liberal in what you accept." In this particular case it means it would be wise for an implementation to accept messages with any content-transfer-encoding, but restrict generation to the 7-bit format required by this memo. This will allow future compatibility in the event the Internet SMTP framework becomes 8-bit friendly.

#### 4. OpenPGP encrypted data

Before OpenPGP encryption, the data is written in MIME canonical format (body and headers).

OpenPGP encrypted data is denoted by the "multipart/encrypted" content type, described in [1], and MUST have a "protocol" parameter value of "application/pgp-encrypted". Note that the value of the parameter MUST be enclosed in quotes.

The multipart/encrypted MUST consist of exactly two parts. The first MIME body part must have a content type of "application/pgp-encrypted". This body contains the control information. A message complying with this standard MUST contain a "Version: 1" field in this body. Since the OpenPGP packet format contains all other information necessary for decrypting, no other information is required here.

The second MIME body part MUST contain the actual encrypted data. It must be labeled with a content type of "application/octet-stream".

Example message:

```
From: Michael Elkins <elkins@aero.org>
To: Michael Elkins <elkins@aero.org>
Mime-Version: 1.0
Content-Type: multipart/encrypted; boundary=foo;
    protocol="application/pgp-encrypted"
```

```
--foo
Content-Type: application/pgp-encrypted
```

```
Version: 1
```

```
--foo
Content-Type: application/octet-stream
```

```
-----BEGIN PGP MESSAGE-----
```

```
Version: 2.6.2
```

```
hIwDY32hYGCE8MkBA/wOu7d45aUxF4Q0RKJprD3v5Z9K1YcRJ2fve87lMlDlx4Oj
eW4GDdBfLbJE7VUpp13N19GL8e/AqbyyjHH4aS0YoTk10QQ9nnRvjY8nZL3MPXSZ
g9VGQxFeGqzykzmykU6A26MSMexR4ApeeON6xzzWfo+0yOqAq6lb46wsvldZ96YA
AABH78hyX7YX4uT1tNCWEIIBoqqvCeIMpp7UQ2IzBrXg6GtukS8NxbukLeamqVW3
lyt2lDY0juLzcmNe/JNsD9vDVCvOOG3OCi8=
=zzaA
```

```
-----END PGP MESSAGE-----
```

```
--foo--
```

## 5. OpenPGP signed data

OpenPGP signed messages are denoted by the "multipart/signed" content type, described in [2], with a "protocol" parameter which MUST have a value of "application/pgp-signature" (MUST be quoted) if the message contains a single signature, or "multipart/mixed" if the message contains two or more signatures [8]. In the latter case, each OpenPGP signature is denoted using the content-type "application/pgp-signature" inside the multipart/mixed.

var1        The "micalg" parameter MUST contain exactly one hash-symbol. This hash-symbol identifies the message integrity check (MIC) algorithm used to generate the subsequent signature. Hash-symbols are constructed from the text names registered in [4] or according to the mechanism defined in that document by converting the text name to lower case and prefixing it with the four characters "pgp-".

var1        Currently defined values are "pgp-md5", "pgp-sha1", "pgp-ripemd160", "pgp-md2", "pgp-tiger192", and "pgp-haval-5-160".

- var2        The "micalg" parameter for the "application/pgp-signature" protocol MUST have a value of "pgp-`<hash-symbol>`", where `<hash-symbol>` identifies the Message Integrity Check (MIC) algorithm used to generate the signature. The currently-defined values for `<hash-symbol>` are "md5" for the MD5 checksum, and "sha1" for the SHA-1 algorithm (FIPS 180-1) [5]: compliant implementations MUST be able to accept and generate MD5 signature-hashes and MUST be able to accept and generate SHA-1 signature-hashes.
- var2        Note: new `<hash-symbol>` values may be registered by sending email to `<new-pgp-hash-value-reg@iana.org>`. The listing of current values may be obtained by sending email to `<pgp-hash-values@iana.org>`.

The multipart/signed body MUST consist of exactly two parts. The first part contains the signed data in MIME canonical format, including a set of appropriate content headers describing the data.

The second body MUST contain the OpenPGP digital signature(s). It MUST be labeled with a content type of "application/pgp-signature" if there is a single signature, or "multipart/mixed" if there are two or more signatures.

When the OpenPGP digital signature is generated:

- (1) The data to be signed must first be converted to its content-type specific canonical form. For text/plain, this means conversion to an appropriate character set and conversion of line endings to the canonical `<CR><LF>` sequence.
- (2) An appropriate Content-Transfer-Encoding is then applied. In particular, if any line begins with the string "From", it is strongly recommended that Quoted-Printable encoding be applied and that at least one of the characters in the string is encoded using the hexadecimal coding rule. This is because many mail transfer agents treat "From " (the word "from" followed immediately by a space character) as the start of a new message and thus insert a right angle-bracket (>) in front of any line beginning with "From" to distinguish this case, invalidating the signature. In addition, line endings in the encoded data MUST use the canonical `<CR><LF>` sequence where appropriate (note that the canonical line ending may or may not be present on the last line of encoded data and MUST NOT be included in the signature if absent).

- (3) MIME content headers are then added to the body, each ending with the canonical <CR><LF> sequence.
- (4) As described in [1], the digital signature MUST be calculated over both the data to be signed and its set of content headers.
- (5) The signature MUST be generated detached from the signed data so that the process does not alter the signed data in any way.

Note: The accepted OpenPGP convention is for signed data to end a <CR><LF> sequence. Note that the <CR><LF> sequence immediately preceding a MIME boundary delimiter line is considered to be part of the delimiter in [3], 5.1. Thus, it is not part of the signed data preceding the delimiter line. An implementation which elects to adhere to OpenPGP convention has to make sure it inserts a <CR><LF> pair on the last line of the data to be signed and transmitted (signed message and transmitted message MUST be identical).

Example message:

```
From: Michael Elkins <elkins@aero.org>
To: Michael Elkins <elkins@aero.org>
Mime-Version: 1.0
Content-Type: multipart/signed; boundary=bar; micalg=pgp-md5;
  protocol="application/pgp-signature"

--bar
& Content-Type: text/plain; charset=iso-8859-1
& Content-Transfer-Encoding: quoted-printable
&
& =AlHola!
&
& Did you know that talking to yourself is a sign of senility?
&
& It's generally a good idea to encode lines that begin with
& From=20because some mail transport agents will insert a greater-
& than (>) sign, thus invalidating the signature.
&
& Also, in some cases it might be desirable to encode any =20
& trailing whitespace that occurs on lines in order to ensure =20
& that the message signature is not invalidated when passing =20
& a gateway that modifies such whitespace (like BITNET). =20
&
& me

--bar
```

Content-Type: application/pgp-signature

-----BEGIN PGP MESSAGE-----

Version: 2.6.2

```
iQCVAwUBMJrRF2N9oWBghPDJAQE9UQQAt17LuRVndBjrk4EqYBIb3h5QXIX/LC//
jJV5bNvkZIGPIcEmI5iFd9boEgvpHtIREEqLQRkYNoBActFBZmh9GC3C041WGq
uMbrbxc+nIs1TIKlA08rVi9ig/2Yh7LFrK5Ein57U/W72vgSxLhe/zhdfolT9Brn
HOxEa44b+EI=
```

=ndaj

-----END PGP MESSAGE-----

--bar--

The "&"s in the previous example indicate the portion of the data over which the signature was calculated.

Upon receipt of a signed message, an application MUST:

- (1) Convert line endings to the canonical <CR><LF> sequence before the signature can be verified. This is necessary since the local MTA may have converted to a local end of line convention.
- (2) Pass both the signed data and its associated content headers along with the OpenPGP signature to the signature verification service.

## 6. Encrypted and Signed Data

Sometimes it is desirable to both digitally sign and then encrypt a message to be sent. This protocol allows for two methods of accomplishing this task.

### 6.1. RFC1847 Encapsulation

In [2], it is stated that the data is first signed as a multipart/signature body, and then encrypted to form the final multipart/encrypted body. This is most useful for standard MIME-compliant message forwarding.

Example:

```
Content-Type: multipart/encrypted;
  protocol="application/pgp-encrypted"; boundary=foo
```

```
--foo
```

```
Content-Type: application/pgp-encrypted
```

```
Version: 1
```

```
--foo
```

```
Content-Type: application/octet-stream
```

```
-----BEGIN PGP MESSAGE-----
```

```
& Content-Type: multipart/signed; micalg=pgp-md5
&   protocol="application/pgp-signature"; boundary=bar
```

```
&
```

```
& --bar
```

```
& Content-Type: text/plain; charset=us-ascii
```

```
&
```

```
& This message was first signed, and then encrypted.
```

```
&
```

```
& --bar
```

```
& Content-Type: application/pgp-signature
```

```
&
```

```
& -----BEGIN PGP MESSAGE-----
```

```
& Version: 2.6.2
```

```
&
```

```
& iQCVAwUBMJrRF2N9oWBghPDJAQE9UQQAtl7LuRVndBjrk4EqYBIb3h5QXIX/LC//
```

```
& jJV5bNvkZIGPIcEmI5iFd9boEgvpirHtIREEqLQRkYNoBActFBZmh9GC3C04lWGq
```

```
& uMbrbxc+nIs1TIKlA08rVi9ig/2Yh7LFrK5Ein57U/W72vgSxLhe/zhdfoIT9Brn
```

```
& HOxEa44b+EI=
```

```
& =ndaj
```

```
& -----END PGP MESSAGE-----
```

```
&
```

```
& --bar--
```

```
-----END PGP MESSAGE-----
```

```
--foo--
```

(The text preceded by '&' indicates that it is really encrypted, but presented as text for clarity.)

## 6.2. Combined method

The OpenPGP packet format [1] describes a method for signing and encrypting data in a single OpenPGP message. This method is allowed in order to reduce processing overhead and increase compatibility with non-MIME implementations of OpenPGP. The resulting data is



formatted as a "multipart/encrypted" object as described in Section 4.

Messages which are encrypted and signed in this combined fashion are REQUIRED to follow the same canonicalization rules as for multipart/signed objects.

It is explicitly allowed for an agent to decrypt a combined message and rewrite it as a multipart/signed object using the signature data embedded in the encrypted version.

#### 7. Distribution of OpenPGP public keys

Content-Type: application/pgp-keys  
Required parameters: none  
Optional parameters: none

This is the content type which SHOULD be used for relaying public key blocks.

#### 8. Security Considerations

Use of the protocols defined in this document has the same security considerations as OpenPGP, and is not known to either increase or decrease the security of messages using it; see [3], [4] for more information.

#### 9. Notes

"PGP" and "Pretty Good Privacy" are registered trademarks of Network Associates, Inc.

#### 10. Acknowledgements

This draft document relies on the work of the IETF's OpenPGP Working Group's definitions of the OP Message Format. The OP message format is currently described in RFC 2440 [4].

Special thanks are due: to Philip Zimmermann for his original and ongoing work on PGP; to Charles Breed for originally proposing the formation of the OpenPGP Working Group; and to Steve Schoenfeld for helpful feedback during the draft process. The authors would also like to thank the engineers at Pretty Good Privacy, Inc (now Network Associates, Inc), including Colin Plumb, Hal Finney, Jon Callas, Mark Elrod, Mark Weaver and Lloyd Chambers, for their technical commentary.

Additional thanks are due to Jeff Schiller and Derek Atkins for their continuing support of strong cryptography and PGP freeware at MIT; to Rodney Thayer of Sable Technology; to John Noerenberg, Steve Dorner and Laurence Lundblade of the Eudora team at QUALCOMM, Inc; John Gilmore, Hugh Daniel and Fred Ringel (at Rivertown) for their timely critical commentary; and to the international members of the IETF's OpenPGP mailing list, including William Geiger, Lutz Donnerhacke and Kazu Yamamoto. The idea to use multipart/mixed with multipart/signed has been attributed to James Galvin. Finally, our gratitude is due to the many members of the "Cypherpunks," "Coderpunks" and "PGP-USERS" mailing lists and the many users of PGP worldwide for helping keep the path to privacy open.

#### 11. Addresses of the Authors and OpenPGP Working Group Chair

The OpenPGP working group can be contacted via the current chair:

John W. Noerenberg II  
Qualcomm, Inc.  
5775 Morehouse Dr.  
San Diego CA 92121 USA  
Tel: +1 619 658 3510  
Email: jwn2@qualcomm.com

The principal authors of this draft are:

Michael Elkins  
Network Associates, Inc.  
3415 S. Sepulveda Blvd Suite 700  
Los Angeles CA 90034 USA  
Tel: +1.310.737.1623  
Fax: +1.310.737.1755  
Email: michael\_elkins@nai.com

Raph Levien  
University of California at Berkeley  
579 Soda Hall  
Berkeley CA 94720 USA  
Tel: +1.510.642.6509  
Email: raph@acm.org

Dave Del Torto  
CryptoRights Foundation  
80 Alviso Street, Mailstop: CRF  
San Francisco CA 94127 USA  
Tel: +1.415.334.5533, vm: #2  
Email: ddt@cryptorights.org, ddt@openpgp.net

Thomas Roessler  
Nordstrasse 99  
D-53111 Bonn  
Germany  
Tel: +49-228-638007  
Email: roessler@guug.de

#### References

- [1] Callas, J., Donnerhackle, L., Finney, H., Thayer, R., "OpenPGP Message Format", RFC 2440, November 1998.
- [2] Galvin, J., Murphy, G., Crocker, S., and N. Freed, "Security Multiparts for MIME: Multipart/Signed and Multipart/Encrypted", RFC 1847, October 1995.
- [3] Freed, N., Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", RFC 2046, November 1996
- [4] Galvin, J., Murphy, G., Crocker, S., and N. Freed, "MIME Object Security Services", RFC 1848, October 1995.
- [5] Atkins, D., Stallings, W., and P. Zimmermann, "PGP Message Exchange Formats", RFC 1991, August 1996.
- [6] Elkins, M., "MIME Security with Pretty Good Privacy (PGP)", RFC 2015, October 1996.
- [7] Freed, N., "Gateways and MIME Security Multiparts", RFC 2480, January 1999.
- [8] Roessler, T., Del Torto, D., Levien, R., "Multiple Signatures using Security Multiparts", draft-ietf-multsig-00.txt, January 2000.

#### Full Copyright Notice

Copyright (C) The Internet Society 2000. All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other

Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

